

Amendments to the Claims

Please amend claims 1-4, 8 and 9, and add new claim 12 as shown in the following listing of claims. This listing of claims will replace all prior versions,
5 and listings, of claims in the application.

1. (currently amended) A method, for a receiver (105, 107, 109, 111) adapted for receiving broadcasted signal (103) from a broadcaster (101), of handling the execution of a first independent feature, where at least a part of feature data (A, B, C, D), needed to execute said first independent feature, is comprised in said broadcasted signal as data relating to a first Xlet, wherein said data relating to said first Xlet further comprise feature data needed to execute at least a second independent feature (A, B, C, D), and wherein said feature data are broadcasted as data carousels, the method comprising the steps of:

- receiving instructions identifying said first feature, wherein the instructions further comprise an identification that the identified first feature is to be executed,
- loading, from at least one of the data carousels ~~the data carousel~~, the feature data related to said first feature into memory of said receiver, the feature data related to said first feature and said second feature being part of said first Xlet,
and
- executing said identified feature.

2. (currently amended) A method according to claim 1, wherein the step of loading, from at least one of the data carousels ~~the data carousel~~, the feature data related to said first feature, into memory of said receiver comprises the step of:

- mounting the data carousel comprising the feature data needed to execute said first independent feature, and
- creating a class loader being dedicated to said first feature.

3. (currently amended) A method according to claim 1, wherein the method

further comprises the steps of:

- receiving instructions identifying a feature, wherein the instructions further comprise an identification that the identified feature is to be terminated,
- terminating said feature, and
- removing the feature data, related to said identified feature, from memory of said receiver.

4. (currently amended) A method according to claim 3, wherein the step of removing the feature data, related to said identified feature, from memory of said receiver comprises the steps of:

- unmounting the data carousel comprising the feature data needed to execute said first independent feature and removing it from the memory, and
- removing all references to the class loader being dedicated to said first feature and removing it from the memory.

5. (original) A method according to claim 1, wherein the instructions identifying said first independent feature is received from the broadcaster.

6. (original) A method according to claim 1, wherein the instructions identifying said first independent feature is received from a user communicating with the receiver.

7. (original) A method according to claim 6, wherein the receiver presents an identification of at least a part of said broadcasted independent features to said user and the instructions identifying said first independent feature is based on said presentation.

8. (currently amended) A method, for a broadcaster adapted to transmit a broadcast signal, of broadcasting a first independent feature to be executed by a receiver, where at least a part of the feature data needed to execute said first independent feature is comprised in said broadcaster signal as data relating to a first Xlet, wherein said data relating to said first Xlet further comprise feature data

needed to execute at least a second independent feature, and wherein said feature data are broadcasted as data carousels, the method comprising the step of broadcasting feature data needed to execute a third independent feature, where said third independent feature enables the receiver to handle the execution of said first independent feature by:

- receiving instructions identifying said first feature, wherein the instructions further comprise an identification that the identified first feature is to be executed,
- loading, from at least one of the data carousels ~~the data carousel~~, the feature data related to said first feature, into memory of said receiver, the feature data related to said first feature, said second feature and said third feature being part of said first Xlet, and
- executing said identified feature.

9. (currently amended) A receiver (105, 107, 109, 111, 206) adapted for receiving broadcasted signal from a broadcaster (101, 200), where the receiver is adapted for handling the execution of a first independent feature, where at least a part of the feature data needed to execute said first independent feature is comprised in said broadcaster signal as data relating to a first Xlet, wherein said data relating to said first Xlet further comprise feature data needed to execute at least a second independent feature, and wherein said feature data are broadcasted as data carousels, the receiver comprising:

- means (401) for receiving instructions identifying said first feature, wherein the instructions further comprise an identification that the identified first feature is to be executed,
- means (401) for loading, from at least one of the data carousels ~~the data carousel~~, the feature data related to said first feature, into memory of said receiver, the feature data related to said first feature and said second feature being part of said first Xlet, and
- means (401) for executing said identified feature.

10. (canceled).

11. (canceled).

12. (new) A method according to claim 1, further comprising receiving a feature table that comprises a feature name field, a carousel identification field and a startup class name field.